

Electric Stone Radiators

Specifications – Designer range

Designer range electric radiators are manufactured from a single 30mm panel of natural stone. The panel is grooved and fitted with a durable insulated electric heating element then covered with a thin insulating marble/clay mixture ensuring optimal heat insulation. The radiators have a built-in safety fuse, which regulates the surface temperature and protects the heating element against damages.

The surface finish is available as polished, brushed, honed and sandblasted. All radiators are supplied ready for connection to a suitable 220-240V power supply. However, for best performance and more efficient energy consumption, it is recommended that they be connected to and controlled by a room thermostat.

The radiators are mounted on the wall using durable discrete metal mounting brackets.

Below is the table of full technical specifications of the products.

<i>Dimensions (mm)</i>	<i>Power (W)</i>	<i>Heating Capacity* (m³)</i>	<i>Voltage (V)</i>	<i>Current (A)</i>	<i>Weight (kg)</i>
560x410	400	≈ 12	220-240	1.50	20
810x410	600	≈ 23	220-240	2.60	30
1115x340	600	≈ 23	220-240	2.60	30
1025x500	800	≈ 30	220-240	3.50	37
1170x580	1100	≈ 43	220-240	4.80	55
1260x580	1400	≈ 52	220-240	6.10	60
1350x650	1600	≈ 58	220-240	6.90	63

- *Bracket depth - 45mm, stone thickness – 30mm, wall to front surface distance- 75mm*
- *Horizontal or vertical installation must be specified at the time of purchase*
- *Maximum operating temperature 90C°*
- *5-year guarantee included*
- *Natural stone patterns may vary*

*Approximate heating requirements in the table above are only an estimate of the maximum amount of space the radiators can heat. Their values can be affected by numerous factors such as insulation, double glazing, number and size of windows, outside temperature, number of cold days etc...Please contact us for more information and more accurate estimate of heating requirement.